



MODEL: **A2300N**

THERMAXX ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

Temperature Capacity
-20°C

Cubic Capacity
4.56m³

BODY DIMENSION			
External length	2300mm	Side door	Passenger side single door 1300 x 600mm
External width	1800mm	Rear door	Double - (left opens first)
External height	1460mm	Front wall frame	Universal to suit off engine drive units
Internal length	2140mm	Side step	Optional
Internal width	1640mm	Rear step	Powdercoated rear light assembly bar
Internal height	1300mm	Cargo track	Optional
Pallet loading	1 Pallet capacity	Floor	One piece aluminium ricegrain
Fitted body weight		*450kg	Internal light
PANELS THICKNESS			1 LED sensor light
Roof/floor	80mm	Refrigeration	Thermo King SV400
Front wall	80mm		
Side walls/rear doors	80mm		



Thermal efficiency 'K' VALUE .37 W/m²K tested to Australian Standard AS4982

Standard Inclusions

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED lights
- Moulded plastic mud guards
- Options available to suit customer requirements

Model No: A2300N-BCEI

