



MODEL: **A5500P**

THERMAXX ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

Temperature Capacity
-20°C

Cubic Capacity
28.21m³

BODY DIMENSION			Side door
External length	5500mm		Passenger side pallet door 2200 x 1400mm
External width	2490mm		
External height	2400mm		
Internal length	5320mm		Rear door
Internal width	2410mm		Front wall frame
Internal height	2200mm		
Pallet loading	8 Pallet capacity		Side step
Fitted body weight	*2090kg		Rear step
PANELS THICKNESS			Cargo track
Roof/floor	100mm		
Front wall	100mm		Floor
Side walls/side doors	40mm		Internal light
Rear doors	80mm		Refrigeration



Thermal efficiency 'K' VALUE .57 W/m²K tested to Australian Standard AS4982

Standard Inclusions

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor lights
- Rubber bump stops
- Rear/side grab handles
- Recessed load restraint track
- Moulded plastic mud guards
- Alloy kick panel
- Options available to suit customer requirements

Model No: A5500P - BDEHI

