



MODEL: **A9000P**

THERMAXX ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

Temperature Capacity
-20°C

Cubic Capacity
52.08m³

BODY DIMENSION

External length	9000mm
External width	2490mm
External height	2650mm
Internal length	8820mm
Internal width	2410mm
Internal height	2450mm
Pallet loading	14 Pallet capacity

Fitted body weight

***3420kg**

PANELS THICKNESS

Roof/floor	100mm
Front wall	100mm
Side walls/side doors	40mm
Rear doors	80mm

Side door

N/A

Rear door

Double (left opens first)

Front wall frame

Universal to suit diesel drive units

Side step

N/A

Rear step

Heavy duty crash bar

Cargo track

2 recessed row @ 800-1400mm
2 shoring bars

Floor

One piece aluminium ricegrain

Internal light

4 LED sensor light

Refrigeration

Thermo King T-1200R



Thermal efficiency 'K' VALUE .55 W/m²K tested to Australian Standard AS4982

Standard Inclusions

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor lights
- Rubber bump stops
- Rear/side grab handles

Model No: **A9000P - BEHI**

