



MODEL: **A4200P**

**THERMAXX**

ADVANTAGE

THE ADVANTAGE IS TO YOUR BOTTOM LINE

Temperature Capacity  
**-20°C**

Cubic Capacity  
**19.38m³**

#### BODY DIMENSION

External length **4200mm**  
External width **2490mm**  
External height **2200mm**

Internal length **4020mm**  
Internal width **2410mm**  
Internal height **2000mm**

Pallet loading **6 Pallet capacity**

#### Fitted body weight

**\*1428kg**

#### PANELS THICKNESS

Roof/floor **100mm**  
Front wall **100mm**  
Side walls/side doors **40mm**  
Rear doors **80mm**

#### Side door

Passenger side single door  
2000 x 800mm

#### Rear door

Double - (left opens first)

#### Front wall frame

Universal to suit off engine  
drive units

#### Side step

Fixed rung step

#### Rear step

Fixed plank step

#### Cargo track

1 recessed row @ 800mm  
1 shoring bar

#### Floor

One piece aluminium ricegrain

#### Internal light

2 LED sensor light

#### Refrigeration

Thermo King SV600



Thermal efficiency 'K' VALUE .55 W/m<sup>2</sup>K tested to Australian Standard AS4982

#### Standard Inclusions

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor lights
- Rubber bump stops

#### Model No: **A4200P-BCEHI**

- Rear/side grab handles
- Recessed load restraint track
- Moulded plastic mud guards
- Alloy kick panel
- Options available to suit customer requirements

